

## O.C.-FORM® 150 UL, PAN

O.C.-FORM® 150 UL, PAN is a polyurethane soft foam impregnated with modified acrylates and laminated with a carbon fibre fleece.

### Characteristics of O.C.-FORM® 150 UL, PAN

- sound absorption and structure-borne sound insulation
- sealing against dust, draught and moisture, decoupling of components
- density of 150 kg/m<sup>3</sup>
- resistant against ageing, weather conditions and hydrolysis

### Fire protection according to DIN EN 45545-2

#### classified as R22/R23-HL2

Classification report: 2017-1037

#### Applications

The surface coating provides an additional mechanical protection and prevents from penetration of sticky acrylates in the assembly condition.  
It makes it ideal for the use as a service aperture sealing.

#### Dimensions

thickness of 5,5, 10, 15, 20, 25, 30, 35, 40, 45, 50 mm

#### Forms of delivery

sheets, tapes, die-cut parts and contour-cut parts, with self-adhesive

#### Storage stability

unlimited, with self-adhesive (SK) 12 months  
(at temperatures of +5 °C to +35 °C, keep dry and free of dust,  
no direct exposure to sunlight or other heat sources)

#### Environment

free of heavy metal (Pb, Hg, Cd, Cr VI), prohibited substances as mentioned in GADSL- and RoHS-list and brominated flame retardant (PBB, PBDE, penta- and octabromine derivatives)